

HOV5 SERIES

HOV5-04HP | HOV5-04UV | HOV5-05SP | HOV5-05UV | HOV5-14SP | HOV5-14UV

CVap Holding Cabinet: Includes C-Touch Control, HACCP Temperature Downloads, and Convection Holding.

SHORT FORM SPECS

Shall be Winston CVap Holding Cabinet, model _____. Unit to utilize a C-Touch control with processor to control calibration-free thermistors to adjust evaporator and air temperatures in 1°F increments. Features must include a minimum of eight programmable channels which are lockable, USB HACCP download for temperature monitoring and convection fan.

CONFIGURATIONS


Countertop: Shallow depth to allow placement on standard 30" countertop. Also can be fitted with 1" wheels for under counter use.

Half-Sized: Easily mobile versions, allowing operator to see over cabinet when transporting. Most half-sized units are also stackable for increased versatility. Some versions available for under counter use with 1" wheels.

Full-Sized: Provides maximum capacity for high volume operators.

CVAP ADVANTAGE

There is a humidified holding cabinet, and there is CVap. CVap incorporates the precision of sous vide cooking with the ability to control how crispy or soft you want a food to stay. We've got volumes of science and data to back us up, but only so much space here. So, if you want to learn more, go to our website, www.winstonfoodservice.com, and geek out with us.



CTC - C-Touch Control HD - HACCP Temp Download
 WC - Wireless Connectivity CM - Convection Mode
 FP - Food Probe AP - Audio

Cabinet Specifications

HOV5-04HP | HOV5-04UV | HOV5-05SP | HOV5-05UV | HOV5-14SP | HOV5-14UV

MODEL NUMBER DESCRIPTIONS

SERIES

PAN CONFIGURATION

EQUIPMENT TYPES

HO = HOLDING
CH = COOK/HOLD
RT = RETHERM
UB = UNIVERSAL BIN

H O V 5 - 0 4 H P







EQUIPMENT TYPE

TECHNOLOGY

PAN CAPACITY

PAN CONFIGURATIONS

HP = HALF PAN
SP = SHEET PAN
UV = UNIVERSAL

MODEL #	CAPACITY*			EXTERIOR DIMENSIONS**			ELECTRICAL						SHIP WEIGHT LBS(KG)	AVAILABLE OPTIONS
	SHEET PAN (18" x 26")	HALF SHEET PAN (18" x 13")	HOTEL PAN (12" x 20" x 2.5")	HEIGHT IN.(MM)	DEPTH IN.(MM)	WIDTH IN.(MM)	VOLTS	PHASE	WATTS	AMPS	NEMA***	INT'L		
HOV5-04HP	N/A	4	4	34(864)	26.8(681)	20.2(511)	120	1	1408	11.75	5-20P 	Call Factory	160 (73)	A,B,C,E,F,J,L,M,N,O,P
HOV5-04UV	4	8	8	35.8(908)	34.5(876)	28(711)	120	1	2292	19.1	5-20P 	Call Factory	198(90)	A,B,C,E,F,H,I,J,M,N,O,P
HOV5-05SP	5	10	N/A	39.3(997)	34.2(867)	24.5(622)	120	1	2292	19.1	5-20P 	Call Factory	235(107)	A,B,C,D,E,F,G,H,I,J,M,N,O,P
HOV5-05UV	5	10	10	39.3(997)	34.5(876)	28(711)	120	1	2292	19.1	5-20P 	Call Factory	250(113)	A,C,D,E,F,G,H,I,J,M,N,O,P
HOV5-14SP	14	28	N/A	73.2(1857)	34.5(876)	25(635)	120	1	2292	19.1	5-20P 	Call Factory	394(179)	A,C,E,F,H,I,J,K,M,N,O,P
HOV5-14UV	14	28	28	73.2(1857)	34.5(876)	28(711)	120	1	2292	19.1	5-20P 	Call Factory	420(190)	A,C,E,F,H,I,J,K,M,N,O,P

*Capacity- Determined by 3.5" (89mm) adjustable spacing, with a load limit of 65lb (29.25kg) per rack. | **Exterior Dimensions- Based on use of standard supplied 3" Heavy Duty plate casters. 1" wheels, 5" casters, and 4" legs are available as an option on most models and will impact dims. | ***NEMA- Supplied with 84" (2134mm) (minimum) power cord and plug. The input average of current did not exceed the allowable amperage for the circuit listed.

CONTROL: C-Touch control with vapor and air temperatures to be adjusted in 1°F increments. Processor controlled calibration-free thermistors, accurate within +/- 2°F. Control allows for eight programmable (and lockable) channels, accommodates software updates via USB.

MATERIALS: To be commercial and institutional grade stainless steel interior and exterior.

DOORS: Insulated field-reversible door with magnetic handles. Full-sized units to include two dutch doors. Doors may be specified with windows, pass-through, or a combination of both.

WATER FILL: Operated manually with low water detection. Auto-fill optional. Low mineral potable water recommended, otherwise use deionizer/demineralizer to minimize corrosion damage.

INSTALLATION REQUIREMENTS: Units to be installed with 2" (51mm) clearance on sides and may not be installed within proximity to anything omitting heat that would allow the exterior of the Winston cabinet to exceed surface temperatures of >200°F. Refer to owner's manual for specific installation requirements. Generally, this equipment is not required to be installed under Type 1 or Type 2 Hoods; however, check local health and fire codes for requirements specific to the location.

INDUSTRY COMPLIANT: Equipment complies with domestic and most international requirements; such as UL, C-UL, UL Sanitation, CE, MEA, and others.

WARRANTY: Limited one-year warranty (excludes gaskets, lamps/lights, hoses, power cord, glass panels, and evaporator). Warranty disclaimer for improper cleaning, installation, and/or maintenance. Ask for complete warranty disclosure.

SPECIFY THE FOLLOWING WHEN ORDERING:

Standard (No additional cost):

- Hinge Preference: Left or right hinge.

Available Options (Additional cost):

- | | |
|--------------------------------|----------------------|
| A. 5" Plate Casters | I. Transport |
| B. 1" Wheels | J. Locking Handle |
| C. Window | K. Security Package |
| D. Flip-Up Lexan Door | L. 4" Legs |
| E. Pass Through | M. 6" Legs |
| F. Pass Through - Window | N. Auto Water Fill |
| G. Pass Through - Flip-Up Door | O. Extended Warranty |
| H. Full Perimeter Bumper | P. Cord Wrap |

Accessories & Supplies (Additional cost):

- | | |
|----------|---|
| PS2206-4 | Wire rack-chrome (4-pack) |
| PS2206-5 | Wire rack-chrome (5-pack) |
| PS2938-4 | Wire rack-stainless steel (4-pack) |
| PS2980-2 | Wire rail (2-pack) |
| PS2935-2 | Wire rail - 04HP (2-pack) |
| PS2429 | External water filter for auto water fill |
| PS2696 | Mobile water removal system |
| PS3171 | Leg and shelf kit for 04UV and 05UV |
| PS3174 | Stacking kit for 04UV and 05UV |
| PS3167 | Drain kit for stacked pair |
| PS3173 | Top Extension 8.5" |

BUY WINSTON SERVICE PARTS, ACCESSORIES, AND SUPPLIES ONLINE!

Factory direct at winstonind.com/buyparts